



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/840,082	04/24/2001	Joo Soo Lim	049128-5006	2174
9629	7590	09/13/2007		
MORGAN LEWIS & BOCKIUS LLP 1111 PENNSYLVANIA AVENUE NW WASHINGTON, DC 20004			EXAMINER QI, ZHI QIANG	
			ART UNIT	PAPER NUMBER
			2871	
			MAIL DATE	DELIVERY MODE
			09/13/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary

Application No.

09/840,082

Applicant(s)

LIM ET AL.

Examiner

Mike Qi

Art Unit

2871

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 03 August 2007.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-3,9,11-13,19 and 21 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-3,9,11-13,19 and 21 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All b) ☐ Some * c) ☐ None of:
- 1) ☒ Certified copies of the priority documents have been received.
 - 2) ☐ Certified copies of the priority documents have been received in Application No. _____.
 - 3) ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- 3) ☐ Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____

- 4) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____
- 5) ☐ Notice of Informal Patent Application
- 6) ☐ Other: _____

DETAILED ACTION

Remarks

The applicant's arguments filed on Aug. 3, 2007 stated claims 1-3, 9,11-13,19,21 and 22 are pending in this application. However, the amended claims are claims 1-3,9,11-13, 19 and 21. Therefore, the examination is for claims 1-3, 9, 11-13, 19 and 21 set forth below.

Claim Rejections - 35 USC § 103

1. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

2. Claims 1-3, 9, 11-13 and 19 are rejected under 35 U.S.C. 103(a) as being unpatentable over Applicant admitted prior art (AAPA) in view of US 6,297,862 (Murade) and US 5,339,181 (Kim et al).

Regarding claims 1, 9, 11 and 19, **AAPA** teaches (paragraphs 0006 – 0010; Figs. 1-3) a conventional liquid crystal display comprising:

- a pixel electrode (10) at a pixel area between a gate line (14) and data line (13);
- a switching device (thin film transistor TFT) (12) at an intersection between the gate line (14) and the data line (13), and having drain electrode (7) is made of metal connected to the pixel electrode (10) (see Fig.2) as a first metal film ;

Art Unit: 2871

- a light-shielding member (black matrix) (11) as a first light-shielding member covering the switching device (TFT) (12) and also on the first metal film (the drain electrode (7));
- a charging device (a storage capacitor 19 between the gate line 14 as the lower electrode and the upper metal thin film 15 as the upper electrode or a second metal film overlapping the pixel electrode 10) on the gate line (14), therefore, the charging device is a storage capacitor (19) including the upper electrode (metal) (15) (a second metal film overlapping the pixel electrode) and the gate line (14) and a gate insulating layer (4) (dielectric layer) between the gate line (14) and the upper electrode (15); or forming a charging device including upper electrode (15) made of metal (second metal film on the rear substrate and overlapping the pixel electrode) over the gate line (14) and a dielectric layer (gate insulating layer 4 as shown in Fig.3);
- a light-shielding member (black matrix) (11) covering the drain electrode (7) of the switching device (TFT) (12) (the first metal thin film) functions as the first light-shielding member or the first dummy black matrix;
- a light-shielding member (black matrix) (11) covering the charging device (19) (the storage capacitor) also functions as the second light-shielding member or the second dummy black matrix;

(concerning claims 1, 9 and 19)

- drain electrode (7) made of metal (first metal thin film) connected to the pixel electrode (10) (see Fig.2);

Art Unit: 2871

- upper electrode (15) made of metal (second metal thin film) on the gate line (14) and a gate insulating layer (4) (dielectric layer) forming a charging device (capacitor) and overlapping the pixel electrode (10);
- a light-shielding member (black matrix) (11) on a front substrate (2) opposed to the rear substrate (1), and at a boundary portion between pixel areas (10) (see Figs.1 and 2);
- a light-shielding member (black matrix) (11) for blocking light incident onto the drain electrode (7) (first metal thin film) of the switching device (TFT) (12) and for blocking light incident onto the storage capacitor upper electrode (15) (second metal thin film).

AAPA does not expressly disclose the first light-shielding member (black matrix) extending from ends of the first metal (drain electrode) into the pixel area and the second light-shielding member (black matrix) extending from ends of the second metal film (upper electrodes of the storage capacitor) into the pixel area, such that the black matrix (first light-shielding member and second light-shielding member) completely covering the switching device (TFT) and the charging device (storage capacitor), so as to provide a margin sufficient to block light incident on the first and second metal films (drain electrodes and upper electrodes of the storage capacitor).

Murade teaches (col.7, line 11 – col.9, line 67; col.16, line 43 – col.17, line 53; Figs.1, 2, 11-14, 20) that the shielding film (black matrix 6) is formed around the pixel, and the shielding film (black matrix 6) completely covering the switching device (TFT, such as the source/drain regions 1a and 1b as shown in Figs. 1 and 2) and extending

from the drain region into the pixel area, and the light shielding member (black matrix 6) completely covering and extending over the drain/source region, and the light shielding member (black matrix 6) also extending over the upper electrode of a storage capacitor (any two conductive layers and an insulating layer would constitute a capacitor) such as the data line (3) made of metal (aluminum) (see col.7, lines 28-29) and gate line (2) (or there is a metal film 7) and insulating film (13, 12, 11) that constitutes a capacitance (charging device or storage capacitor) (see Fig.2) , and that is sufficient to block light incident onto the drain/source region (the metal thin film), and the light incident on the liquid crystal device does not affect the TFT performance, and a bright, high quality images will be ensured (see col.6, lines 4-6).

Since such light-shielding arrangement would sufficiently block the light incident to the TFT, so as to minimize the leakage current of the TFT. Murade indicates (col.9, lines 58 –67) that such black matrix (6) as shown in Fig.2 completely covering (overlapping and extending) the TFT including the drain electrode and storage capacitance and the side portion of the pixel electrode would present a display of high quality images free from image degrading effect such as cross-talk.

Further, **Kim** teaches (col.3, line 40 – col.5, line 25; Fig.2A) that a liquid crystal display device having a first electrode (10) of each storage capacitor C (as the second metal film of this application), the gate line (1) and the insulating layer (2) forming a storage capacitor C; and the black matrix light shielding layer (20) completely covering the switching device (TFT) and extending from ends of the drain/source electrode (5a, 5b) (as first metal film of this application) into the pixel area (4) as shown in Fig.2A and

2B; and the black matrix light shielding layer (20) on the electrode (10) (as the second metal film of this application) completely covering the storage capacitor C and extending from ends of the electrode (10) (as the second metal film of this application), and the storage capacitor C overlapping the pixel electrode (4) as shown in Fig.2A and 2B. Kim further teaches (col.5, lines 9-14) that the electrode (10) of each storage capacitor C substantially surrounding each pixel electrode so as to serve as an additional light shielding layer, such that the light shielding structure (completely covering the TFT and the storage capacitor) provides a margin sufficient to block light incident onto the TFT and the storage capacitor, and that would have been at least obvious.

Therefore, it would have been obvious to those skilled in the art at the time the invention was made to modify the liquid crystal display device of AAPA with the teachings of extending the light-shielding film completely covering the thin film transistor and completely covering the storage capacitor as taught by Murada and Kim, since the skilled in the art would be motivated for minimizing the leakage current of the TFT, improving the display contrast, and presenting a display of high quality images free from image degrading effect such as cross-talk so as to provide a margin sufficient to block light incident onto the TFT and the storage capacitor.

Regarding claims 2 and 12, AAPA teaches (paragraphs 0006 – 0010; Figs. -3) that the light-shielding member (11) is at a front substrate (2) opposed to a rear substrate (1) which includes the switching device (TFT 12), pixel electrode (10), the charging device (storage capacitor 19), and a liquid crystal layer between the two substrates.

Regarding claims 3 and 13, AAPA discloses (paragraphs 0006 – 0010; Figs. 1-3) that the light-shielding member is a black matrix.

3. Claim 21 is rejected under 35 U.S.C. 103(a) as being unpatentable over AAPA Murade and Kim as applied to claims 1-3, 9, 11-13 and 19 above, and further in view of US 6,266,117 (Yanagawa et al).

Regarding claim 21, AAPA, Murada and Kim teach the invention set forth above except for that the material of the light-shielding member is an organic material containing a black pigment,

Yanagawa teaches (co.7, lines 1-2) that the light shielding film is made of an organic resin in which, e.g., black pigment is dispersed, so that using the organic resin containing a black pigment as a light shielding member would be a routine skill in the art, and that was common and known in the art as the light shielding property of the organic material containing a black pigment to absorb light.

Therefore, it would have been obvious to those skilled in the art at the time the invention was made to modify the liquid crystal display device of AAPA, Murada and Kim with the teachings of using an organic material containing a black pigment to form a light shielding member as taught by Yanagawa, since the skilled in the art would be motivated for absorbing light because the organic material containing a black pigment having the property to absorb light.

Response to Arguments

4. Applicant's arguments filed on Aug. 3, 2007 have been fully considered but they are not persuasive.

In response to applicant's arguments that the references fail to teach or suggest "a back matrix completely covering the thin film transistor and the storage capacitor at a boundary portion between pixel areas" it is respectfully pointed out that Murade teaches (col.7, line 11 – col.9, line 67; col.16, line 43 – col.17, line 53; Figs.1, 2, 11-14, 20) that the shielding film (black matrix 6) is formed around the pixel, and the shielding film (black matrix 6) completely covering the switching device (TFT, such as the source/drain regions 1a, 1b, as shown in Figs. 1 and 2) and extending from the drain region into the pixel area, and the light shielding member (black matrix 6) completely covering and extending over the drain/source region, and the light shielding member (black matrix 6) also extending over the upper electrode of a storage capacitor (any two conductive layers and an insulating layer would constitute a capacitor) such as the data line (3) made of metal (aluminum) and gate line (2) (or there is a metal film 7) and insulating film (13, 12, 11) that constitutes a capacitance (charging device or storage capacitor), and that is sufficient to block light incident onto the drain/source region (the metal thin film), and the light incident on the liquid crystal device does not affect the TFT performance, and a bright, high quality images will be ensured.

The reference Murade described in the summary of the invention that a black matrix can be safely omitted which does not mean without black matrix in the liquid crystal display device, and the Figs 1 and 2 clearly show the black matrix (6) completely

Art Unit: 2871

covering and extending overlapping the drain electrode and a capacitance and the side of the pixel electrode.

Further Kim teaches (col.3, line 40 – col.5, line 25; Fig.2A) that a liquid crystal display device having a first electrode (10) of each storage capacitor C (as the second metal film of this application), the gate line (1) and the insulating layer (2) forming a storage capacitor C; and the black matrix light shielding layer (20) completely covering the switching device (TFT) and extending from ends of the drain/source electrode (5a, 5b) (as first metal film of this application) into the pixel area (4) as shown in Figs.2A and 2B; and the black matrix light shielding layer (20) on the electrode (10) (as the second metal film of this application) completely covering the storage capacitor C and extending from ends of the electrode (10) (as the second metal film of this application), and the storage capacitor C overlapping the pixel electrode (4) as shown in Figs.1A and 2B. Kim further teaches (col.5, lines 9-14) that the electrode (10) of each storage capacitor C substantially surrounding each pixel electrode so as to serve as an additional light shielding layer, such that the light shielding structure (completely covering the TFT and the storage capacitor) provides a margin sufficient to block light incident onto the TFT and the storage capacitor, and that would have been at least obvious.

Conclusion

5. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

6. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Mike Qi whose telephone number is (571) 272-2299. The examiner can normally be reached on M-T 7:30 am-6:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Nelms can be reached on (571) 272-1787. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2871

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.



Mike QI
Sep. 10, 2007